





Nitonakrętki neoprenowe (antywibracyjne)



NORMA	MATERIAŁ	KLASA	POWŁOKA
	Korpus: neopren (kautczuk syntetyczny) Wkładka: mosiądz		

d_{nom}	M3	M4	M5				M6	
d_1	7,9	7,9	9,6				12,7	
d_2	11	11	12,7	14			16,0	19,1
k	1,4	1,4	0,9	0,9	1,3		1,3	4,75
l	12,6	12,6	14,1	21,5	26,1	39,8	16,0	21,1
e	0,4 – 4,0	0,4 – 4,0	0,4 – 4,9	4 – 11,6	7,9 – 16,0	20,5 – 30,0	0,4 – 2,8	0,8 – 4,7
*	max 8,3	max 8,3	max 9,9				max 13	

d_{nom}	M6		M8			M10	M12
d_1	12,7	13,0	15,9		18,0	20,0	24,0
d_2	16,3	16,0	22,1		20,0	22,5	27,0
k	2,0	1,3	3,2	5,72	1,6	1,3	1,3
l	26,7	35,0	18,3	27,9	50,0	55,0	80,0
e	6,4 – 11,5	11,5 – 23,0	0,4 – 4,0	3,9 – 9,5	15,0 – 39,0	19,0 – 40,0	38,0 – 64,0
*	max 13		max 16,2		max 18,3	max 20,3	max 24,3